


SWITCHING APPLICATION.
INTERFACE CIRCUIT AND DRIVER CIRCUIT APPLICATION.



FEATURES

- With Built-in Bias Resistors.
- Simplify Circuit Design.
- Reduce a Quantity of Parts and Manufacturing Process.
- High Packing Density.
- Suffix U : Qualified to AEC-Q101.
ex) KRA760E-RTK/HU

EQUIVALENT CIRCUIT



EQUIVALENT CIRCUIT (TOP VIEW)



MAXIMUM RATING (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CBO}	-50	V
Collector-Emitter Voltage	V _{CEO}	-50	V
Emitter-Base Voltage	V _{EBO}	-5	V
Collector Current	I _C	-100	mA

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector Power Dissipation	P _C *	200	mW
Junction Temperature	T _j	-55~150	°C
Storage TemperatureRange	T _{stg}	-55~150	°C

* Total Rating.

ELECTRICAL CHARACTERISTICS (Ta=25°C)


CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		I _{CBO}	V _{CB} =-50V, I _E =0	-	-	-100	nA
Emitter Cut-off Current		I _{EBO}	V _{EB} =-5V, I _C =0	-	-	-100	nA
DC Current Gain		h _{FE}	V _{CE} =-5V, I _C =-1mA	120	-	-	
Collector-Emitter Saturation Voltage		V _{CE(sat)}	I _C =-10mA, I _B =-0.5mA	-	-0.1	-0.3	V
Transition Frequency		f _T *	V _{CE} =-10V, I _C =-5mA	-	250	-	MHz
Input Resistor	KRA760E	R _i	-	3.29	4.7	6.11	kΩ
	KRA761E			7	10	13	
	KRA762E			70	100	130	
	KRA763E			15.4	22	28.6	
	KRA764E			32.9	47	61.1	

Note : * Characteristic of transistor only.

MARK SPEC

TYPE	KRA760E	KRA761E	KRA762E	KRA763E	KRA764E
MARK	PK	PM	PN	PO	PP

Marking









KRA760E~KRA764E

ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC			SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Switching Time	Rise Time	KRA760E	t_r	V_O =-5V V_{IN} =-5V R_L =1k Ω	-	0.2	-	μ s
		KRA761E			-	0.065	-	
		KRA762E			-	0.4	-	
		KRA763E			-	0.1	-	
		KRA764E			-	0.15	-	
	Storage Time	KRA760E	t_{stg}		-	2.0	-	
		KRA761E			-	1.7	-	
		KRA762E			-	3.0	-	
		KRA763E			-	2.0	-	
		KRA764E			-	1.5	-	
	Fall Time	KRA760E	t_f		-	0.3	-	
		KRA761E			-	0.3	-	
		KRA762E			-	1.7	-	
		KRA763E			-	0.8	-	
		KRA764E			-	1.5	-	

KRA760E~KRA764E



KRA760E~KRA764E

