


SWITCHING APPLICATION.
INTERFACE CIRCUIT AND DRIVER CIRCUIT APPLICATION.

FEATURES


- With Built-in Bias Resistors.
- Simplify Circuit Design.
- Reduce a Quantity of Parts and Manufacturing Process.
- High Packing Density.

EQUIVALENT CIRCUIT




BIAS RESISTOR VALUES

TYPE NO.	R1(k Ω)	R2(k Ω)
KRC657U	10	47
KRC658U	22	47
KRC659U	47	22



EQUIVALENT CIRCUIT (TOP VIEW)



MAXIMUM RATING (Ta=25 °C)


CHARACTERISTIC		SYMBOL	RATING	UNIT
Output Voltage	KRC657U ~659U	V_O	50	V
Input Voltage	KRC657U	V_I	30, -6	V
	KRC658U		40, -7	
	KRC659U		40, -15	
Output Current	KRC657U ~659U	I_O	100	mA
Power Dissipation		P_D^*	200	mW
Junction Temperature		T_j	-55~150	°C
Storage Temperature Range		T_{stg}	-55~150	°C

* Total Rating.

MARK SPEC

TYPE	KRC657U	KRC658U	KRC659U
MARK	NH	NI	NJ

Marking









KRC657U~KRC659U

ELECTRICAL CHARACTERISTICS (Ta=25 °C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT	
Output Cut-off Current		KRC657U ~659U	$I_{O(OFF)}$	$V_O=50V, V_I=0$	-	-	500	nA
DC Current Gain	KRC657U		G_I	$V_O=5V, I_O=10mA$	80	150	-	
	KRC658U				80	150	-	
	KRC659U				70	140	-	
Output Voltage		KRC657U ~659U	$V_{O(ON)}$	$I_O=10mA, I_I=0.5mA$	-	0.1	0.3	V
Input Voltage (ON)	KRC657U		$V_{I(ON)}$	$V_O=0.2V, I_O=5mA$	-	1.2	1.8	V
	KRC658U				-	1.8	2.6	
	KRC659U				-	3.0	5.8	
Input Voltage (OFF)	KRC657U		$V_{I(OFF)}$	$V_O=5V, I_O=0.1mA$	0.5	0.75	-	V
	KRC658U				0.6	0.88	-	
	KRC659U				1.5	1.82	-	
Transition Frequency		KRC657U ~659U	f_T^*	$V_O=10V, I_O=5mA$	-	200	-	MHz
Input Current	KRC657U		I_I	$V_I=5V$	-	-	0.88	mA
	KRC658U				-	-	0.36	
	KRC659U				-	-	0.16	
Switching Time	Rise Time	KRC657U	t_r	$V_O=5V, V_{IN}=5V$ $R_L=1k \Omega$	-	0.05	-	μS
		KRC658U			-	0.12	-	
		KRC659U			-	0.26	-	
	Storage Time	KRC657U	t_{stg}		-	2.0	-	
		KRC658U			-	2.4	-	
		KRC659U			-	1.5	-	
	Fall Time	KRC657U	t_f		-	0.36	-	
		KRC658U			-	0.4	-	
		KRC659U			-	0.41	-	
Input Resistor	KRC657U		R1	-	7	10	13	k
	KRC658U				15.4	22	28.6	
	KRC659U				32.9	47	61.1	
Resistor Ratio	KRC657U		R2/R1	-	3.7	4.7	5.7	
	KRC658U				1.7	2.1	2.6	
	KRC659U				0.37	0.47	0.57	


Note : * Characteristic of Transistor Only.

KRC657U~KRC659U




KRC657U~KRC659U

$G_I - I_O$



$G_I - I_O$



$G_I - I_O$

