

Bias Resistor Built-in TRANSISTOR

KRC402UL is designed to suit for switching application, interface circuit and driver circuit application


FEATURES

- With Built-in Bias Resistors.
- Simplify Circuit Design.
- Reduce a Quantity of Parts.
- Reduce Manufacturing Process.
- High Packing Density.


APPLICATION

- Digital Application.
- Control of IC input.
- General Purpose.


PACKAGE DIMENSION (ULP-3(1))



EQUIVALENT CIRCUIT



MARKING CODE



PRODUCT DATASHEET

Epitaxial Planar Transistor - KRC402UL

MAXIMUM RATING (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Output Voltage	V_o	50	V
Input Voltage	V_i	30, -10	V
Output Current	I_o	100	mA
Power Dissipation	P_D *	250	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-50 ~ 150	°C

* Package mounted on a ceramic board(7x5x0.6mm).




ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Cut-off Current		$I_{O(OFF)}$	$V_o=50V, V_i=0$	-	-	500	nA
DC Current Gain		G_I	$V_o=5V, I_o=10mA$	50	80	-	-
Output Voltage		$V_{O(ON)}$	$I_o=10mA, I_i=0.5mA$	-	0.1	0.3	V
Input Voltage (ON)		$V_{I(ON)}$	$V_o=0.2V, I_o=5mA$	-	1.8	2.4	V
Input Votlage (OFF)		$V_{I(OFF)}$	$I_o=5V, I_o=0.1mA$	1.0	1.2	-	V
Transition Frequency		f_T *	$I_o=10V, I_o=5mA$	-	200	-	MHz
Input Current		I_i	$V_i=5$	-	-	0.88	mA
Switching Time	Rise Time	t_r	$V_o=5V, V_{IN}=5V, R_L=1k\Omega$	-	0.05	-	μs
	Storage Time	t_{stg}		-	2.0	-	
	Fall Time	T_f		-	0.36	-	
Input Resistor		R_1	-	7	10	13	k Ω
Resistor ratio		R_1/R_2	-	0.8	1.0	1.2	-

* Characteristic of Transistor Only.

PRODUCT DATASHEET

Epitaxial Planar Transistor - KRC402UL






PRODUCT DATASHEET

Epitaxial Planar Transistor - KRC402UL

PACKAGE DIMENSION

(ULP-3(1))



DIM	MILLIMETERS
A	1.0±0.05
B	0.6±0.05
C	0.50±0.05
D	0.51±0.04
E	0.16±0.04
F	0.26±0.04
G	0.65 BSC
H	0.35 BSC
J	0.03 Max

PRECAUTION ON USING KEC PRODUCTS

1. The products described in this data are intended to be used in general-purpose electronic equipment.
(Office equipment, telecommunication equipment, measuring equipment, home appliances)
2. When you intend to use these products with equipment or device which require an extremely high of reliability and special applications (such as automobile, air travel aerospace, transportation equipment, life support, system and safety devices) in which special quality and reliability and the failure or malfunction of products may directly jeopardize or harm the human body or damage to property and any application other than the standard application intended, please be sure to consult with our sales representative in advance.
3. On designing your application, please use product within the ranges guaranteed by KEC for maximum rating, operating supply voltage range, heat radiation characteristics and other characteristics. User shall be responsible for failure or damage when used beyond the guaranteed ranges.
4. The technical information described in this data is limited to showing representative characteristics and applied circuit examples of the products and it does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
5. What are described in the data may be changed without any prior notice to reflect new technical development. Please confirm that you have received the latest product standards or specification before final design, purchase or use.
6. Although KEC is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. KEC shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by KEC.

For additional information,
please contact your local Sales Representative.

SOUTH KOREA (Headquarters)
KEC CORPORATION
PHONE : +82-2-2025-5000
sales@kec.co.kr

JAPAN
KEC JAPAN CO.,LTD.
PHONE : +81-03-5475-2691
kec_jp@kec.co.kr

SINGAPORE
KEC SINGAPORE PTE., LTD.
PHONE : +65-6748-7372(#102)
kec_twn@kec.co.kr

THAILAND
KEC THAILAND BANGKOK OFFICE
PHONE : +66-2-576-1484~5
kec_th@kec.co.kr

CHINA
KEC SHANGHAI CO.,LTD.
PHONE : +86-21-5490-2277
kec_sh@kec.co.kr

KEC SHENZHEN OFFICE
PHONE : +86-755-8882-9198
kec_hk@kec.co.kr

KEC TIANJIN OFFICE
PHONE : + 86-21-5490-2277
kec_sh@kec.co.kr

HONG KONG
KEC HK CORP. LTD
PHONE : +852-2249-3734
kec_hk@kec.co.kr

TAIWAN
KEC TAIWAN CO.,LTD.
PHONE : +886-2-2515-8359
kec_twn@kec.co.kr

U.S.A
KEC AMERICA CORP.
PHONE : +1-714-259-0662
kec_a@kec.co.kr

