


PS03PSUL2 is designed to protect signal lines from electrical over stress(EOS). It has excellent clamping voltage & surge capability.

FEATURES

- Transient protection for signal lines to
 - IEC61000-4-2(ESD) : Air mode $\pm 30\text{kV}$ /Contact mode $\pm 30\text{kV}$
 - IEC61000-4-5(Surge) : 7A ($t_p=8/20\mu\text{s}$)
- Low capacitance $C_T = 2.0\text{pF}(\text{Max})$
- Uni-directional, symmetrical working voltage up to : $V_{RWM} = 3.3\text{V}$
- Ultra small Size $1.0 \times 0.6 \times 0.4\text{mm}$
- Low reverse current : 100nA Max ($V_R=3.3\text{V}$)


PACKAGE DIMENSION (ULP-2(3))




APPLICATIONS

- USB3.0, 10/100/1000 Ethernet, DVI
- MDDI Port
- LCD-Display, Camera
- GPS/FM Antennas
- LVDS
- High speed data lines

PIN CONFIGURATION



MARKING CODE



ORDERING INFORMATION

PART NUMBER	QTY PER Reel	Reel SIZE
PS03PSUL2-RTL	10,000	7 inch


PRODUCT DATASHEET

Single Line TVS Diode– PS03PSUL2

MAXIMUM RATING (Ta=25℃)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Peak Pulse Power(tp=8/20μs)	P _{PK}	65	W
Peak Pulse Current(tp=8/20μs)	I _{PP}	7	A
Junction Temperature	T _J	150	℃
Storage Temperature	T _{STG}	-55 ~ 150	℃

DEFINITIONS OF ELECTRICAL CHARACTERISTIC SYMBOL




ELECTRICAL CHARACTERISTICS (Ta=25℃)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Reverse Stand-Off Voltage	V _{RWM}	-	-	-	3.3	V
Reverse Leakage Current	I _R	V _{RWM} =3.3V	-	-	100	nA
Breakdown Voltage	V _{BR}	I _t =1mA	4.5	-	7	V
Total Capacitance	C _T	V _R =0V, f=1MHz	-	-	2.0	pF
Clamping Voltage	V _C	I _{PP} =1A, tp=8/20μs (IEC61000-4-5)	-	5.3	8.5	V
		I _{PP} =7A, tp=8/20μs (IEC61000-4-5)	-	6.1	9.3	
		I _{TLP} =4A, tp=100ns	-	7	-	V
		I _{TLP} =16A, tp=100ns	-	11.2	-	
Dynamic Resistance	R _{DYN}	I _{TLP} =4A to 16A, tp=100ns	-	0.35	-	Ω
Electrostatic Discharge	V _{ESD}	IEC61000-4-2	Air	±30	-	kV
			Contact	±30	-	

PRODUCT DATASHEET
Single Line TVS Diode– PS03PSUL2


NON-REPETITIVE PEAK PULSE POWER VS.
PULSE TIME




POWER DERATION CURVE




REVERSE CURRENT VS. BREAKDOWN
VOLTAGE




REVERSE LEAKAGE CURRENT VS.
REVERSE VOLTAGE



TOTAL CAPACITANCE VS. REVERSE
VOLTAGE




PEAK PULSE CURRENT VS. CLAMPING
VOLTAGE




PRODUCT DATASHEET

Single Line TVS Diode– PS03PSUL2


TRANSMISSION LINE PULSE CURRENT VS.
CLAMPING VOLTAGE




POWER DERATION CURVE



PACKAGE INFORMATION (ULP-2(3))



RECOMMENDED PAD DIMENSION



PRECAUTION ON USING KEC PRODUCTS

1. The products described in this data are intended to be used in general-purpose electronic equipment (Office equipment, telecommunication equipment, measuring equipment, home appliances)
2. When you intend to use these products with equipment or device which require an extremely high of reliability and special applications (such as automobile, air travel aerospace, transportation equipment, life support, system and safety devices) in which special quality and reliability and the failure or malfunction of products may directly jeopardize or harm the human body or damage to property and any application other than the standard application intended, please be sure to consult with our sales representative in advance.
3. On designing your application, please use product within the ranges guaranteed by KEC for maximum rating, operating supply voltage range, heat radiation characteristics and other characteristics. User shall be responsible for failure or damage when used beyond the guaranteed ranges.
4. The technical information described in this data is limited to showing representative characteristics and applied circuit examples of the products and it does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
5. What are described in the data may be changed without any prior notice to reflect new technical development. Please confirm that you have received the latest product standards or specification before final design, purchase or use.
6. Although KEC is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. KEC shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by KEC.

For additional information,
please contact your local Sales Representative.

SOUTH KOREA (Headquarters)
KEC CORPORATION
PHONE : +82-2-2025-5000
sales@kec.co.kr

JAPAN
KEC JAPAN CO.,LTD.
PHONE : +81-03-5475-2691
kec_jp@kec.co.kr

SINGAPORE
KEC SINGAPORE PTE., LTD.
PHONE : +65-6748-7372(#102)
kec_twn@kec.co.kr

THAILAND
KEC THAILAND BANGKOK OFFICE
PHONE : +66-2-576-1484~5
kec_th@kec.co.kr

CHINA
KEC SHANGHAI CO.,LTD.
PHONE : +86-21-5490-2277
kec_sh@kec.co.kr

KEC SHENZHEN OFFICE
PHONE : +86-755-8882-9198
kec_hk@kec.co.kr

KEC TIANJIN OFFICE
PHONE : +86-22-2330-7562
kec_sh@kec.co.kr

HONG KONG
KEC HK CORP. LTD
PHONE : +852-2249-3734
kec_hk@kec.co.kr

TAIWAN
KEC TAIWAN CO.,LTD.
PHONE : +886-2-2515-8359
kec_twn@kec.co.kr

U.S.A
KEC AMERICA CORP.
PHONE : +1-714-259-0662
kec_a@kec.co.kr

