


SWITCHING TYPE POWER SUPPLY APPLICATIONS.

FEATURES

- Low Profile Surface Mount Package.
- Low Power Loss, High Efficiency.
- For Use in Low Voltage, High Frequency inverters, Free Wheeling, and Polarity Protection Applications.

APPLICATION

- Switching Power Supply.
- Reversed Battery Connection Protection.
- DC/DC Converter.
- Cellular Phones.




MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	60	V
Average Output Rectified Current	I_O	1	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	I_{FSM}	25	A
Power Dissipation	P_D^*	700	mW
Junction Temperature	T_j	-40 ~ 150	°C
Storage Temperature Range	T_{stg}	-40 ~ 150	°C

* Mounted on a glass epoxy board (of 1 × 1 inch)

Marking




ELECTRICAL CHARACTERISTICS (Ta=25 °C)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	V_{FM}	$I_{FM}=1.0A$	-	0.55	0.6	V
Repetitive Peak Reverse Current	I_{RRM}	$V_{RRM}=60V$	-	-	1	mA
Total Capacitance	C_T	$V_R=0V, f=1.0MHz$	-	120	-	pF
Thermal Resistance	$R_{th(j-a)}$	Junction to Ambient	-	-	178.6	°C/W

USFB16L

$I_F - V_F$



$C_T - V_R$



$I_{FSM} - \text{CYCLE CHARACTERISTICS}$

