

SWITCHING MODE POWER SUPPLY APPLICATION. CONVERTER & CHOPPER APPLICATION.

FEATURES

- Average Output Rectified Current
: $I_O=30A$
- Repetitive Peak Reverse Voltage
: $V_{RRM}=100V$
- Low Forward Voltage
- Low Reverse Current
- Molding Compound Flammability Rating : UL 94V-0
- Pb-Free, Halogen-Free, RoHs Compliant

MAXIMUM RATING ($T_a=25^{\circ}C$)



CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	100	V
Average Output Rectified Current (Note)	I_O	30	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	I_{FSM}	160	A
Junction Temperature	T_j	-40 ~ 150	$^{\circ}C$
Storage Temperature Range	T_{stg}	-55 ~ 150	$^{\circ}C$

Note : average forward current of centertap full wave connection

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}C$)


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage (Note)	V_{FM}	$I_{FM}=1A$	-	0.40	-	V
		$I_{FM}=7.5A$	-	0.58	-	
		$I_{FM}=15A$	-	0.74	0.77	
Repetitive Peak Reverse Current (Note)	I_{RRM}	$V_{RRM}=\text{Rated}$	-	5	200	μA
Junction Capacitance (Note)	C_j	$V_R=5V, f=1MHz$	-	1.0	-	nF
Thermal Resistance (Note)	$R_{th(j-c)}$	Junction to Case	-	-	6.0	$^{\circ}C/W$

Note : A value of one cell




TMBRD30100CT

$I_F - V_F$



$I_R - V_R$



$C_T - V_R$

