

General Description

KEC Field Stop Trench IGBTs offer low switching losses, high energy efficiency and short circuit ruggedness.

It is designed for applications such as motor control, uninterrupted power supplies(UPS), general inverters.

FEATURES

- High speed switching
- High ruggedness, temperature stable behavior
- Short Circuit Withstand Times 10us
- Extremely enhanced avalanche capability

ORDERING INFORMATION

FULL NAME	PACKAGE	SUFFIX
KGF30N60KDA-U/P	TO-247	-
KGF30N60KDA-U/PE	TO-247(E)	Added code "E" to TO-247(E)

MAXIMUM RATING (Ta=25)




CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Emitter Voltage	V_{CES}	600	V
Gate-Emitter Voltage	V_{GES}	± 20	V
Collector Current	I_C	@Tc=25	60 A
		@Tc=100	30 A
Pulsed Collector Current	I_{CM}^*	90	A
Diode Continuous Forward Current	@Tc=25	I_F	30 A
Diode Maximum Forward Current		I_{FM}^*	90 A
Maximum Power Dissipation	P_D	@Tc=25	178 W
		@Tc=100	71 W
Maximum Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 to + 150	

*Repetitive rating : Pulse width limited by max. junction temperature

THERMAL CHARACTERISTIC

CHARACTERISTIC	SYMBOL	MAX.	UNIT
Thermal Resistance, Junction to Case (IGBT)	R_{thJC}	0.7	/W
Thermal Resistance, Junction to Case (DIODE)	R_{thJC}	1.55	/W
Thermal Resistance, Junction to Ambient	R_{thJA}	40	/W

PIN CONNECTION




KGF30N60KDA

ELECTRICAL CHARACTERISTICS (Ta=25)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=250\mu A$	600	-	-	V
Collector Cut-off Current	I_{CES}	$V_{GE}=0V, V_{CE}=600V$	-	-	250	μA
Gate Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$	-	-	± 100	nA
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=3mA$	4.5	5.5	7.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=30A$	-	1.65	2.1	V
		$V_{GE}=15V, I_C=60A$	-	2.25	-	V
		$V_{GE}=15V, I_C=30A, T_C = 125$	-	1.9	-	V
Dynamic						
Total Gate Charge	Q_g	$V_{CC}=300V, V_{GE}=15V, I_C=30A$	-	120	-	nC
Gate-Emitter Charge	Q_{ge}		-	20	-	nC
Gate-Collector Charge	Q_{gc}		-	60	-	nC
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=300V, I_C=30A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 25$ (Note 1)	-	40	-	ns
Rise Time	t_r		-	30	-	ns
Turn-Off Delay Time	$t_{d(off)}$		-	170	-	ns
Fall Time	t_f		-	35	-	ns
Turn-On Switching Loss	E_{on}		-	0.55	0.75	mJ
Turn-Off Switching Loss	E_{off}		-	0.45	0.65	mJ
Total Switching Loss	E_{ts}		-	1.0	1.4	mJ
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=300V, I_C=30A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 125$ (Note 1)	-	40	-	ns
Rise Time	t_r		-	35	-	ns
Turn-Off Delay Time	$t_{d(off)}$		-	180	-	ns
Fall Time	t_f		-	50	-	ns
Turn-On Switching Loss	E_{on}		-	0.55	-	mJ
Turn-Off Switching Loss	E_{off}		-	0.65	-	mJ
Total Switching Loss	E_{ts}		-	1.2	-	mJ
Input Capacitance	C_{ies}	$V_{CE}=30V, V_{GE}=0V, f=1MHz$	-	2350	3100	pF
Output Capacitance	C_{oes}		-	160	-	pF
Reverse Transfer Capacitance	C_{res}		-	95	-	pF
Short Circuit Withstand Time	t_{sc}	$V_{CC}=300V, V_{GE}=15V, T_C=100$	10	-	-	μs
Short Circuit Collector Current	$I_{C(SC)}$	$V_{CC}=300V, V_{GE}=15V, t_{PSC} 10 \mu s$	-	176	-	A

Note 1 : Energy loss include tail current and diode reverse recovery.

Marking



KGF30N60KDA

ELECTRICAL CHARACTERISTIC OF DIODE

CHARACTERISTIC	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Diode Forward Voltage	V_F	$I_F = 30A$	$T_C = 25$	-	1.7	2.5	V
			$T_C = 125$	-	1.75	-	
Diode Reverse Recovery Time	t_{rr}	$V_{CC} = 300V$	$T_C = 25$	-	80	-	ns
			$T_C = 125$	-	120	-	
Diode Peak Reverse Recovery Current	I_{rr}	$I_F = 30A$	$T_C = 25$	-	14	-	A
			$T_C = 125$	-	16	-	
Diode Reverse Recovery Charge	Q_{rr}	$di/dt = 600A/\mu s$	$T_C = 25$	-	620	-	nC
			$T_C = 125$	-	1160	-	

Typical Performance Characteristics

Fig 1. Saturation Voltage Characteristics




Fig 2. Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature




Fig 4. Saturation Voltage vs. V_{GE}




Fig 5. Saturation Voltage vs. V_{GE}





Fig 6. Capacitance Characteristics



KGF30N60KDA

Typical Performance Characteristics (Continued)

Fig 7. Turn-On Characteristics vs. Gate Resistance




Fig 8. Turn-Off Characteristics vs. Gate Resistance




Fig 9. Switching Loss vs. Gate Resistance




Fig 10. Turn-On Characteristics vs. Collector Current




Fig 11. Turn-Off Characteristics vs. Collector Current





Fig 12. Switching Loss vs. Collector Current



Typical Performance Characteristics (Continued)

Fig 13. Gate Charge Characteristics




Fig 14. SOA Characteristics




Fig 15. Turn-Off SOA





Fig 16. Transient Thermal Impedance of IGBT



KGF30N60KDA

Typical Performance Characteristics

Fig 17. Forward Characteristics




Fig 18. Reverse Recovery Current





Fig 19. Reverse Recovery Time



Definition Switching Time & Loss.

Fig 20. Switching Test Circuit




Fig 21. Definition Switching Time & Loss




Fig 22. Definition Diode Switching Time

