

LOW VOLTAGE HIGH SPEED SWITCHING.



FEATURES

- Low Forward Voltage : $V_{F(2)}=0.43V$ (Typ.)
- Small Package : ESC.
- Suffix U : Qualified to AEC-Q101.
ex) KDR377E-RTK/HU

MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum (Peak) Reverse Voltage	V_{RM}	40	V
Reverse Voltage	V_R	40	V
Maximum (Peak) Forward Current	I_{FM}	150	mA
Average Forward Current	I_O	30	mA
Surge Current (10ms)	I_{FSM}	200	mA
Power Dissipation	P_D	150*	mW
Junction Temperature	T_j	125	
Storage Temperature Range	T_{stg}	-55 ~ 125	


* : Mounted on a glass epoxy circuit board of 20 × 20mm,
pad dimension of 4 × 4mm.




ELECTRICAL CHARACTERISTICS (Ta=25 °C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	$V_{F(1)}$	$I_F=1mA$	-	0.29	0.37	V
	$V_{F(2)}$	$I_F=30mA$	-	0.43	0.55	
Reverse Current	I_R	$V_R=40V$	-	-	20	μA
Total Capacitance	C_T	$V_R=1V, f=1MHz$	-	6.0	-	pF

$I_F - V_F$



$I_R - V_R$



$C_T - V_R$

